

VMwar

2V0-41.20 Exam

Professional VMware NSX-T Data Center

Questions & Answers Demo

Version: 6.0

Question: 1

An NSX administrator noticed that the nsxcli command times out after 600 secs of idle time. Which CLI command disables the nsxcli time out value on NSX Manager?

- A. set cli-timeout 0
- B. set cli-timeout enabled
- C. set cli-timeout disabled
- D. set cli-timeout 1

Answer: A

Reference:

" <https://vdc-download.vmware.com/vmwb-repository/dcr-public/cc42e3c1-eb34-4567-a916-147e79798957/8264605c-a5e1-49a8-b603-cc78621eeeab/cli.html#set%20cli-timeout%20%3Ctimeout%3E>
<https://www.virtten.net/2020/06/quick-tip-remove-nsx-t-ssh-and-http-session-timeout/>

Question: 2

An NSX administrator is configuring the KVM hypervisor host as a transport node and wants to apply the Failover Order as a NIC teaming policy.

Which profile allows the administrator to configure the NIC Teaming policy as Failover Order?

- A. N-VDS/VDS Profile
- B. Transport Node Profile
- C. Host Switch Profile
- D. Uplink Profile

Answer: D

Question: 3

Which two choices are prerequisites to configure NSX-T on VDS? (Choose two.)

- A. MTU 1500
- B. MTU 1400
- C. vSphere Distributed Switch 6.5
- D. vSphere Distributed Switch 7.0
- E. MTU 1600

Answer: DE

Reference:

<https://docs.vmware.com/en/VMware-NSX-T-Data-Center/3.0/installation/GUID-BA34FB2A-6780-41C5-B895-F37E5A7B7BAE.html>

Question: 4

Which command is used to display the network configuration of the Tunnel Endpoint (TEP) IP on a bare metal transport node?

- A. ifconfig
- B. tcpdump
- C. debug
- D. ipconfig

Answer: A

Reference:

<https://docs.vmware.com/en/VMware-NSX-T-Data-Center/3.0/installation/GUID-B7E7371E-A9F6-4880-B184-E00A62C0C818.html>

Question: 5

Which three steps are required to create an IPsec VPN tunnel? (Choose three.)

- A. Create an IPsec service.
- B. Add a local endpoint.
- C. Configure an IPsec session.
- D. Configure a distributed firewall policy.
- E. Add a logical switch.

Answer: ABC

Question: 6

An NSX administrator wants to create a Tier-0 Gateway to support equal cost multi-path (ECMP) routing. Which failover detection protocol must be used to meet this requirement?

- A. Beacon Probing (BP)
- B. Host Standby Router Protocol (HSRP)
- C. Bidirectional Forwarding Detection (BFD)
- D. Virtual Router Redundancy Protocol (VRRP)

Answer: C

Question: 7

What are two supported N-VDS modes? (Choose two.)

- A. DPDK Datapath
- B. Overlay Datapath
- C. Secure Datapath
- D. Enhanced Datapath
- E. Standard Datapath

Answer: DE

Reference:

<https://docs.vmware.com/en/VMware-NSX-T-Data-Center/3.0/installation/GUID-37BC3CEF-DCC1-4C6F-960D-CFBB31908D1C.html>

Question: 8

A user is assigned these two roles in NSX Manager:

LB Admin

Network Engineer

What privileges does this user have in the system?

- A. read permissions on all networking services and full access permissions on load balancing features
- B. full access permissions on all networking services and full access permissions on load balancing features
- C. full access permissions on all networking services and read permissions on load balancing features
- D. read permissions on all networking services and read permissions on load balancing features

Answer: B

Question: 9

An NSX administrator has configured a KVM hypervisor as a transport node. Which kernel module on KVM implements a N-VDS?

- A. openvswitch
- B. etherswitch
- C. nsx-vswitch
- D. dyswitch

Answer: A
