Cisco

Exam 300-208

Implementing Cisco Secure Access Solutions

Version: Demo

[Total Questions: 10]

Cisco 300-208 : Practice Test

Question No: 1 CORRECT TEXT

if the user in non-compliant state and want to Get out of guarantine?

Answer: download posture

Question No: 2

You have configured a Cisco ISE 1.2 deployment for self-registration of guest users. What two options can you select from to determine when the account duration timer begins? (Choose two.)

- A. CreateTime
- B. FirstLogin
- C. BeginLogin
- D. StartTime

Answer: A,B

Question No: 3

Which error in a redirect ACL can cause the redirection of an endpoint to the provisioning portal to fail?

- **A.** The redirect ACL is blocking access to ports 80 and 443.
- **B.** The redirect ACL is applied to an incorrect SVI.
- **C.** The redirect ACL is blocking access to the client provisioning portal.
- **D.** The redirect ACL is blocking access to Cisco ISE port 8905.

Answer: A

Question No: 4

Why does Cisco recommend assigning dynamic classification security group tag assignment at the access layer?

Cisco 300-208: Practice Test

- A. Static security group assignments are more scalable.
- **B.** Security group assignment occurs as users enter the network.
- C. To use SXP to transport STG to IP mappings.
- **D.** Security group assignment occurs as users leave the network.

Answer: B

Question No:5

Which two components are required to connect to a WLAN network that is secured by EAP-TLS authentication? (Choose two.)

- A. Kerberos authentication server
- B. AAA/RADIUS server
- C. PSKs
- D. CA server

Answer: B,D

Question No: 6

Security Group Access requires which three syslog messages to be sent to Cisco ISE? (Choose three.)

- A. IOS-7-PROXY_DROP
- B. AP-1-AUTH_PROXY_DOS_ATTACK
- C. MKA-2-MACDROP
- **D.** AUTHMGR-5-MACMOVE
- E. ASA-6-CONNECT_BUILT
- F. AP-1-AUTH_PROXY_FALLBACK_REQ

Answer: B,D,F

Question No:7

Which advanced authentication setting is needed to allow an unknown device to utilize Central WebAuth?

Cisco 300-208: Practice Test

- A. If Authentication failed > Continue
- **B.** If Authentication failed > Drop
- C. If user not found > Continue
- **D.** If user not found > Reject

Answer: C

Question No:8

Refer to the exhibit.

```
device(config)#aaa new-model
device(config)#tacacs-server host 209.165.200.226
device(config)#tacacs-server host 209.165.200.227
device(config)#tacacs-server key 0 $$5@#$%!!1
```

Which three statements about the given configuration are true? (Choose three.)

- **A.** TACACS+ authentication configuration is complete.
- **B.** TACACS+ authentication configuration is incomplete.
- **C.** TACACS+ server hosts are configured correctly.
- **D.** TACACS+ server hosts are misconfigured.
- **E.** The TACACS+ server key is encrypted.
- **F.** The TACACS+ server key is unencrypted.

Answer: B,C,F

Question No:9

How many days does Cisco ISE wait before it purges a session from the active session list if no RADIUS Accounting STOP message is received?

- **A**. 1
- **B.** 5
- **C.** 10
- **D.** 15

Answer: B

Question No: 10

Which two statements about MAB are true? (Choose two.)

- A. It requires a preexisting database of the MAC addresses of permitted devices.
- **B.** It is unable to control network access at the edge.
- C. If MAB fails, the device is unable to fall back to another authentication method.
- **D.** It is unable to link the IP and MAC addresses of a device.
- **E.** It is unable to authenticate individual users.

Answer: A,E