Cisco

Exam 600-211

Implementing Cisco Service Provider Mobility CDMA Networks (SPCDMA)

Verson: Demo

[Total Questions: 10]

Question No: 1

Refer to the exhibit.

```
aaa group default
radius accounting server 10.10.1.100 key certification priority 1
radius accounting server 10.10.2.100 key certification priority 2
radius accounting server 10.10.3.100 key certification priority 3
```

How would HA select a default server for accounting?

- A. Random, HA randomly picks up a server
- B. Round-robin, HA distribute messages across all servers
- **C.** Relative priority, HA selects the highest priority server
- **D.** First-in, HA select a set of servers with highest priority

Answer: C

Question No: 2

What two protocols are used by the HSGW to provide IPv4 address and IPv4 parameter configuration during PDN connection establishment? (Choose two.)

- A. VSNCP
- B. DHCPv4
- C. DNS
- D. VSNP
- E. DHCPv6
- F. TCP

Answer: A,B

Question No: 3

Which access network element is responsible for delivering the IPv4 address and/or IPv6 prefix to the UE?

- A. 3GPP AAA
- B. aAN/ePCF
- C. 3GPP2 AAA
- D. HSGW
- E. PDN-GW

Answer: D

Question No: 4

Which access ruledef configuration can be used to match all traffic destined to port 8080 sourced from the subscriber on the Cisco ASR 5000?

- A. ruledef block_tcp_8080 tcp dst-port = 8080 tcp uplink = TRUE #exit
- **B.** ruledef block_tcp_8080 tcp dst-port != 8080 #exit
- C. ruledef block_tcp_8080
 tcp dst-port = 8080
 tcp downlink = TRUE
 #exit
- **D.** ruledef block_tcp_8080 tcp src-port = 8080 #exit

Answer: A

Question No:5

Which Cisco ASR 5000 CLI options are available actions that can be taken when NAT allocation is in progress?

- A. forward or buffer
- B. drop or continue
- C. buffer or drop
- **D.** buffer or continue

Answer: C

Question No: 6

Which protocol is used during PPP negotiation to assign an IP address to the mobile device for a simple IP call?

- A. LCP
- B. IPCP
- C. CHAP
- D. EAP

Answer: B

Question No:7

What is the default ruledef type on the Cisco ASR 5000 if the rule-application parameter is not defined?

- A. Post-processing ruledef
- **B.** Routing ruledef
- **C.** Charging ruledef
- **D.** Pre-processing ruledef

Answer: C

Question No:8

What command must be used to enable IPSec on the Foreign Agent service for the Cisco ASR 5000?


- A. ikev1 peer-ha <ha address> crypto-map <map name> secret <shared secret>
- B. ikev1 peer-fa <fa address> crypto-map <map name> key <shared key>
- C. ikev1 peer-ha <ha address> crypto-map <map name> key <shared key>
- D. ikev1 peer-fa <fa address> crypto-map <map name> secret <shared secret>

Answer: A


Question No: 9 DRAG DROP

Drag the Cisco ASR 5000 Diameter applications on the left to match the associated interfaces on the right.	
Diameter authentication	Gy interface
Accounting policy for off-line charging	Gx interface
IMS Authorization	Rf interface
Diameter Credit-Control Application	STa interface

Answer:



Explanation:



C:\Users\Kamran\Desktop\image - Copy.jpg

Question No: 10

Which RFC specifies the Diameter base protocol?

A. RFC 6733

B. RFC 6408

C. RFC 3958

D. RFC 4006

Answer: A