

# **Cisco**

## **Exam 600-212**

### **Implementing Cisco Service Provider Mobility LTE Networks (SPLTE)**

**Verson: Demo**

**[ Total Questions: 10 ]**

**Question No : 1**

Which network function converts Voice over LTE voice bearer to PSTN voice bearer?

- A. border gateway control function
- B. media gateway function
- C. multimedia resource function
- D. session border controller function

**Answer: B**

**Question No : 2**

Which two triggers are applicable to partial record closure for the SGW-CDR? (Choose two.)

- A. termination of IP-CAN bearer
- B. abnormal release
- C. S-GW change
- D. MS Time-Zone-Change
- E. PLMN-Change

**Answer: D,E**

**Question No : 3**

Which MME feature can be configured in the call control policy on the Cisco ASR 5000 system?

- A. super-charger feature configuration
- B. sgtp-service association
- C. direct-tunnel feature configuration
- D. RAT frequency selection priority override

**Answer: D**

**Question No : 4**

As per the 3GPP, which value of the AVP Result-Code is sent by the PCRF to indicate that the subscriber profile is not available in its SPR?

- A. 2001
- B. 5002
- C. 4011
- D. 5030

**Answer: D**

**Question No : 5**

Which two methods are used for Lawful Intercept provisioning? (Choose two.)

- A. Stake out provisioning
- B. Camp-on provisioning provisioning
- C. Active call provisioning
- D. Surveillance provisioning
- E. Circuit tap provisioning

**Answer: B,C**

**Question No : 6**

When a subscriber is connected over 3GPP access and is in a local breakout scenario, which interface is used by the PGW for sending downlink data traffic for inbound roaming subscribers?

- A. S12
- B. S10
- C. S5
- D. S8
- E. S2a

**Answer: C**

**Question No : 7**

Which two APN names are recommended by GSMA IR.88 / IR.92 in the Voice over LTE solution? (Choose two.)

- A. Voice
- B. Emergency
- C. SOS
- D. IMS
- E. Video
- F. SIP

**Answer: C,D**

**Question No : 8**

Which two statements apply during the attach procedure on an MME? (Choose two.)

- A. The attach procedure provides an always-on IP connectivity to the subscriber.
- B. Multiple default bearers can be established during the attach procedure.
- C. A dedicated bearer can also be established during the attach procedure.
- D. The additional guti value in the attach request is derived from a PTMSI.
- E. The attach request is always integrity protected.

**Answer: A,C**

**Question No : 9**

Which two statements about the Diameter message direction on the Rf interface are true? (Choose two.)

- A. Diameter Accounting-Request is initiated by S-GW/P-GW to CDF.
- B. Diameter Accounting-Answer is initiated by CDF to S-GW/P-GW.
- C. Diameter Accounting-Request is initiated by S-GW/P-GW to CGF.
- D. Diameter Accounting-Answer is initiated by CGF to S-GW/P-GW.
- E. Diameter Accounting-Request is initiated by S-GW/P-GW to the billing server.
- F. Diameter Accounting-Answer is initiated by the billing server to S-GW/P-GW.

**Answer: A,B**

**Question No : 10 DRAG DROP**

Drag the LTE interface on the left to the node on the right that it operates between.

S3	eNodeB and Serving Gateway
S8	Packet Data Network Gateway and Serving Gateway
S5	Packet Data Network Gateway and Serving Gateway (VPLMN)
S1u	Mobility Management Entity and Serving GPRS Support Node

**Answer:**

Drag the LTE interface on the left to the node on the right that it operates between.

S3	S1u
S8	S5
S5	S8
S1u	S3

**Explanation:**

S1u
S5
S8
S3

C:\Users\Kamran\Desktop\image - Copy.jpg