

SAP

C_HANADEV_16 Exam

**SAP Certified Development Associate - SAP HANA 2.0 SPS04
Exam**

**Questions & Answers
Demo**

Version: 5.0

Question: 1

To comply with the SAP Fiori principles, which view type is recommended by SAP?

- A. JSON
- B. XML
- C. HTML
- D. JavaScript

Answer: B

Question: 2

In an SAPUI5 application, where do you find the reference to sap-ui-core.js?

- A. In the URL to the SAPUI5 application
- B. In the bound attributes data model
- C. In the manifest.json descriptor file
- D. In the bootstrap section of the index.html

Answer: D

Question: 3

You implement a native SAP HANA application using SAP HANA extended application services, advanced mode (XS advanced) and SAPUI5.

Where is the UI rendering executed?

- A. On the XS advanced application server
- B. On the SAPUI5 HTML5 module
- C. On the front-end client device
- D. On the SAP Fiori front-end server

Answer: B

Question: 4

Which of the following are characteristics of SAPUI5? Note; There are 3 correct answers to this question.

- A. Provides device-specific user experience
- B. Supports customer-specific theming
- C. Provides an extensibility concept
- D. Enables responsive application design
- E. Renders the UI on server side

Answer: BCD

Question: 5

What happens if you define a database object in the persistence model and deploy it using the SAP HANA Deployment Infrastructure (HDI)?

- A. The corresponding runtime object is created in the database module of the multi-target application during runtime.
- B. The corresponding runtime object is created in the HDI container on deployment.
- C. A descriptive representation of the object is created in HDI during runtime.
- D. The HDI container is created when the design-time object is saved.

Answer: D

Question: 6

Which GIT command do you use to consolidate all changes from one branch with another branch using a single commit?

- A. Commit
- B. Push
- C. Rebase
- D. Merge

Answer: D

Question: 7

You need to view the data model exposed by an OData V2 service. What must you append to the service URL?

- A. \$servicedefinition
- B. \$schema
- C. \$metadata
- D. \$format

Answer: C

Question: 8

Which of the following SQLScript elements do you use to transform a set of arrays into an intermediate table variable?

- A. SET
- B. UNSET
- C. ARRAY
- D. UNNEST

Answer: D

Question: 9

In an SQLScript procedure, which feature do you use to initialize IN/OUT table parameters?

- A. IS_EMPTY
- B. DEFAULT EMPTY
- C. DEFAULT
- D. SET

Answer: B

Question: 10

You must debug an existing SQLScript procedure in SAP HANA extended application services, advanced model (XS advanced).

What is the valid sequence to debug the procedure?

- A. 1 Select the SQLScript procedure in the project explorer, p. 2 Open the SQLScript console.
3 Set the breakpoint in the code of your SQL procedure.
4 Generate the call to the SQL procedure and execute it.
- B. 1 Select the SQLScript procedure in the database explorer, p. 2 Set the debugger privilege.
3 Set the external breakpoint in the code of your SQL procedure.
4 Run the ABAP program where the SQL procedure is called in debugging mode.
- C. 1 Select the ABAP program where the SQLScript procedure is called in the project explorer. p. 2 Set the external debugger privilege.
3 Set the external breakpoint in the code of your ABAP program.
4 Run the ABAP program in debugging mode.

D. 1 Select the SQLScript procedure in the database explorer. / pv 2 Specify the SQLScript debugger settings in the SQL Debugger.

3 Set the breakpoint in the code of your stored procedure.

4 Generate the call to the SQL procedure and execute it.

Answer: D
