Huawei

H12-831_V1.0 Exam

HCIP-Datacom-Advanced Routing & Switching Technology V1.0

Questions & Answers Demo

Version: 4.0

Question: 1	
In OSPFv3, an LSA whose propagation range is one area haskind. (Fill i	n Arabic numerals only)
	Answer: 9
Explanation:	
Question: 2	
BFDLink state detection at the heart (millisecond) level can be achieved.	
A. right B. wrong	
	Answer: A
Explanation:	
Question: 3	
Which of the following statements about the multicast address used by OSPI	Fv3 is correct?
A. DR routers use FF08::6	
B. All OSPF routers use FF08: 5	
C. All 5PF Routers use FF02:5 D. DRThe router uses FF02::6	
e de la companya della companya della companya de la companya della companya dell	Answer: C, D
Explanation:	
Question: 4	
by executingThe command can completely isolate the second and third layer users of different ports on the same LAN and cannot communicate. (Please use English and lowercase letters to complete the command, and the command cannot be abbreviated)	
·	Answer: (port-isolate
	enable)
Explanation:	
Question: 5	

Explanation:

D. business test	
C. Cutover preparation D. business test	
B. cutover implementation	
A. field defense	
Which of the following operations is not part of the middle stage of dissecti-	on?