

# **Huawei**

**H31-311\_V2.5 Exam**

**HCIA-Transmission V2.5**

**Questions & Answers  
Demo**

# Version: 4.0

---

**Question: 1**

---

When performing fiber cut-off test on an ordinary MSP ring, which of the following alarms will be reported? (Multiple choice).

- A. YOU-AIS
- B. R-LOS
- C. APSJNDI
- D. BD

---

**Answer: B, C**

---

Explanation:

---

**Question: 2**

---

When the bridge uses ivl learning mode, an entry in the MAC address table is created based on the source MAC address and source port of the teach frame. This entry applies to all VLANs

- A. True
- B. False

---

**Answer: B**

---

Explanation:

---

**Question: 3**

---

Compared with dense wavelength division multiplexing (DWDM) systems, crude glass division multiplexing (CWDM) systems provide a certain amount of glass length and transmission distance within (kmkm), which greatly reduces system cost and has strong flexibility

- A. 50
- B. 100
- C. 200
- D. 20

---

**Answer: B**

---

Explanation:

---

**Question: 4**

---

If you group SNCP services with the same source, sink, or route, you can increase the SNCP switching speed

- A. True
- B. Error

---

**Answer: A**

---

Explanation:

---

**Question: 5**

---

The standard Ethernet frame length should not be less than 64 bytes Which of the following factors contribute to this limitation? (Multiple choice).

- A. Minimum transmission distance
- B. Maximum transmission distance
- C. How conflict detection works
- D. MAC address

---

**Answer: B, C**

---

Explanation: