

Delta - Integrating HP ProLiant Server Solutions

Verson: Demo

[Total Questions: 10]

Question No:1

An integrator is preparing tor 3n HP OneView installation. Which software component needs to be installed at the customer site before the integrator can perform the installation?

- A. an ICsp appliance deployed and ready for integration with HP OneView
- B. a server with Windows 2008 R2 installed
- C. Insight control, ready to be upgraded to HP OneView
- D. supported hypervisor for HP OneView deployment

Answer: D

Question No:2

What is a benefit of using 20Gb FlexFabric Converged network adapter (CNA) for the BladeSystems?

A. It allows support tor RDMA over Converged Ethernet (RCOE) when the HP 6125XLG is used in conjunction with the FlexFabric adapter.

B. It delivers 10Gb performance per port with an aggregate 20Gb in a dual-port adapter.

C. The adapter streams converge 10GbE and 16Gb storage simultaneously over the same 20GD port.

D. Performance is delivered through multiple 2/10Gb ports using multiple adapters in a teamed fashion.

Answer: D

Question No:3

A company needs a solution Tor monitoring and diagnosing issues with devices in its data center. The company has the following requirements for the solution:

•It monitors its HP ProLiant Gen6 and Gen9 servers.

•It monitors its HP storage and networking devices.

•It is simple- to set up.

Why should the integrator choose HP Insight Online with HP Insight Remote Support rather than HP insight Online alone as the solution?

- A. it does not require the installation of a local hosting device
- **B.** it is required to monitor Gen9 servers
- C. it supports storage and networking devices
- D. it is required for mixed Gen8 and Gen9 deployments

Answer: C

Question No:4

An integrator needs to deploy an HP OneView appliance to the ESXi Server managed by the vCenter Server.

Which tool can the integrator use to access the vCenter Server?

- A. VNC Console
- B. vSphere Management Assistant
- C. vRealize operations
- D. Web Client

Answer: C

Question No:5

Which is an appropriate use of the HP OneView Dashboard?

- A. to locate a server using a topology map of managed data center components
- B. to determine whether any servers or enclosures have a warning or critical health status
- C. to launch the integrated Lights Out (iLO) interface tor an individual managed server
- D. to check the power utilization of an individual managed server or rack

Answer: B

Question No:6

A customer has an HP ProLiant OL380 Gen9 server with a Smart Array P440ar controller.

The customer needs to add another internal drive cage and create a RAID set using all internal drives. Which HP component should the integrator install in the HP ProLiant DL380 Gen9 server?

- A. HP Smart SAS HBA H240ar Controller
- B. HP PCIe Workload Accelator
- **C.** HP Smart Storage Battery
- D. HP SAS Expander

Answer: D

Question No:7

How does Secure Boot protect against unauthorized operating systems and malware attacks?

A. by validating the Challenge Handshake Authentication Protocol passphrase

B. by integrating with REST API callouts that perform bootloaders encryption

C. by validating that the system only runs digitally signed option ROMs and operating system boot loaders

D. by integrating with different authentication systems, including Kerberos and Active Directory

Answer: C

Question No:8

What is the maximum number of processor cores on an HP ProLiant Gen9 server?

- **A.** 12
- **B.** 14
- **C.** 16
- **D.** 18

Answer: D

Question No:9

A customer needs their HP ProLiant DL380. Gen9 server to automatically report hardware

failures to the HP Support Center.

Which tool should an integrator select to enable automatic reporting?

A. HP OneViewB. Intelligent ProvisioningC. UEFID. Insight online

Answer: D

Question No : 10

A customer has an HP ProLiant DL380 Gen9 server with one processor that has a large RAID 5 SAS Array configured on a P440ar storage controller with a hot spare. During the rebuild process, a second SAS drive failed.

What should the integrator do to help prevent this problem from reoccurring?

- A. Configure a higher Rebuild.
- **B.** Priority Install a second hot spare disk drive.
- **C.** Install more memory in the server.
- **D.** Use the integrated B140i controller.

Answer: B