

Pass Delta - Applying Aruba Switching Fundamentals for Mobility Exam

Questions & Answers Demo

Question: 4

Answer: A

Version: 8.0
Question: 1
What is one requirement to combine Aruba 5400R zl2 Series switches in a Virtual Switching Framework (VSF) fabric?
A. Both of the members must have two management modules. B. The switches must operate in v3-module only mode; any modules of an earlier version are automatically disabled.
C. The interfaces assigned to the VSF link must be pre-configured as part of a link aggregation. D. One of the switches must be an Aruba 5412R switch, while the other member can be any switch in the 5400R series.
Answer: D
A network administrator wants to apply a critical PoE priority to any ArubaOS switch port that connects to an Aruba AP. The priority should be applied dynamically based on LLDP messages received from the AP Which step should the administrator take to meet this goal? A. Configure the PoE usage setting on all ports as //dp. B. Configure the PoE usage setting on all ports as class and make sure that Aruba APs are defined as Class 4 devices. C. Enable the default AP profile bound to the Aruba AP device type. D. Enable LLDP MED TLV extensions on the switch port.
Answer: C
Question: 3
Which solution provides firmware update automation for Aruba APs and switches?
A. Aruba ClearPass B. Aruba Virtual Switching Framework (VSF) C. Aruba Activate D. Aruba AirWave



The exhibit shows settings for a WLAN on an Aruba Instant cluster To which VLAN is wireless user traffic assigned?

- A. to the untagged VLAN on switch ports connected to the Instant APs
- B. to the VLAN defined for wireless users in Aruba AirWave
- C. to the default VLAN defined in the System settings in the Instant
- D. to the default VLAN on switches connected to the Instant APs

Answer: D