

Junos, Associate Exam

Questions & Answers Demo

Version: 6.0

Question: 1	
How many login classes are assignable to a user account?	
A. 3	
B. 2	
C. 4	
D. 1	
	Answer: D
Explanation:	
https://www.juniper.net/documentation/us/en/software/junos/user-aaccess/topics/topic-map/junos-os-login-class.html#:~:text=You%20can%20define%20any%20number,to%20an ount. In Junos OS, each user account can be assigned only one login class. Lethe permissions for users, controlling what they can access and modify helps in maintaining a clear and secure access control mechanism.	%20individual%20user%20acc
Reference:	
Junos OS Documentation on User Accounts and Login Classes.	
Question: 2	
You are asked to view the real-time usage statistics for the busiest inte Junos OS. Which command will achieve this task?	rfaces on a device running
A. monitor traffic absolute-sequence	
B. monitor interface traffic	
C. monitor traffic	
D. show interfaces extensive	
	Answer: B
Explanation:	

To view real-time usage statistics for the busiest interfaces on a device running Junos OS, the correct command is B, "monitor interface traffic." This command provides a dynamic, real-time view of the traffic flowing through the interfaces, allowing administrators to quickly identify and monitor the

busiest interfaces on the device.	
Question: 3	
Which type of device uses the destination IP address to forward packets	?
A. Layer 3 router B. Layer 2 switch C. repeater D. hub	
Explanation:	Answer: A
A Layer 3 router forwards packets based on the destination IP address. It layer of the OSI model and uses routing tables to determine the best pat Layer 2 switches, which forward packets based on MAC addresses, route making them crucial for inter-network communication. Reference: Junos OS Documentation on Routing Fundamentals.	h for packet delivery. Unlike
Question: 4	
You have just increased the MTU size of interface ge-0/0/0 and committee Which command would help you identify the applied MTU change?	ed the configuration.
A. monitor interface ge-0/0/0 B. monitor traffic interface ge-0/0/0 C. show interfaces ge-0/0/0 terse D. show interfaces ge-0/0/0	
	Answer: D
Explanation:	
After increasing the MTU size of an interface and committing the configuration the applied MTU change is D, "show interfaces ge-0/0/0." This confined information about the interface, including the current MTU size, making verifying the applied changes.	nmand displays detailed
Question: 5	
When considering routing policies which two statements are correct?	Shaasa tuua \

When considering routing policies, which two statements are correct? (Choose two.)

- A. Routing policies are applied to interfaces as input or export filters.
- B. An import routing policy for BGP determines which received prefix advertisements are placed in the routing information base.
- C. Policy terms are evaluated from top to bottom with action taken on the first match found.

D. Policy terms are evaluated from top to bottom with the most r	estrictive action taken of all the
matching terms.	
	Answer: BC
Explanation:	

Routing policies in Junos OS are crucial for controlling route advertisements and path selection. The correct answers are B and C. An import routing policy for BGP determines which received prefix advertisements are placed in the routing information base (RIB), and policy terms are evaluated from top to bottom, with action taken on the first match found. This sequential evaluation allows for precise control over routing decisions.